


Butterfly Valves

Lugged Body



Application: Water, Seawater, Sewerage, Air, Oil, Powder, Gas

Working Pressure: CI 230 PSI SS, PP 150 PSI

Test Pressure: Body: CI 350 PSI SS, PP 230 PSI
Seat: CI 250 PSI SS, PP 170 PSI

Temperature: EPDM: -10°C to +120°C
Viton: -10°C to +150°C
PTFE: -10°C to +200°C

CIVBFLW is Watermark Approved

Size (in)	PRODUCT CODE			
	Material	Cast Iron	Cast Iron	Cast Iron
	Seat	NBR	PTFE	EPDM
Flange	E	ANSI 150	E	
2		CIVBFL-050	CIVBFLA-050	CIVBFLW-050
2 1/2		CIVBFL-065	CIVBFLA-065	CIVBFLW-065
3		CIVBFL-080	CIVBFLA-080	CIVBFLW-080
4		CIVBFL-100	CIVBFLA-100	CIVBFLW-100
5		CIVBFL-125	CIVBFLA-125	
6		CIVBFL-150	CIVBFLA-150	CIVBFLW-150
8		CIVBFL-200	CIVBFLA-200	CIVBFLW-200
10		CIVBFL-250		CIVBFLW-250
12		CIVBFL-300		CIVBFLW-300

Size (in)	PRODUCT CODE		
	Material	Cast Iron	Stainless Steel
	Seat	PTFE	PTFE
Flange	E	ANSI 150	
2		CIVBFLP-050	SSVBFLAP-050
2 1/2		CIVBFLP-065	
3		CIVBFLP-080	SSVBFLAP-080
4		CIVBFLP-100	SSVBFLAP-100
6		CIVBFLP-150	SSVBFLAP-150
8		CIVBFLP-200	SSVBFLAP-200
10			SSVBFLAP-250
12			SSVBFLAP-300

Worm Gear Operated



Size (in)	PRODUCT CODE		
	Material	Cast Iron - NBR	Stainless Steel
Seat	E		
2		CIVBFLF-050	
2 1/2		CIVBFLF-065	
3		CIVBFLF-080	
4		CIVBFLF-100	
5		CIVBFLF-125	
6		CIVBFLF-150	
8		CIVBFLF-200	
10		CIVBFLF-250	
12		CIVBFLF-300	
14		CIVBFLF-350	
16		CIVBFLF-400	
18		CIVBFLF-450	
20		CIVBFLF-500	
24		CIVBFLF-600	