

# Butterfly Valves

## Wafer Body



<b>Application:</b>	Water, Seawater, Sewerage, Air, Oil, Powder, Gas
<b>Working Pressure:</b>	CI 230 PSI    SS, PP 150 PSI
<b>Test Pressure:</b>	Body:    CI 350 PSI    SS, PP 230 PSI Seat:    CI 250 PSI    SS, PP 170 PSI
<b>Temperature:</b>	EPDM:    -10°C to +120°C Viton:    -10°C to +150°C PTFE:    -10°C to +200°C

CIVBFWW is Watermarked Approved

Size (in)	PRODUCT CODE			
	Material	Cast Iron	Cast Iron	Cast Iron
	Seat	NBR	EPDM	EPDM
Flange	D&E, DIN, ANSI	E	E	
2		CIVBFW-050	CIVBFE-050	CIVBFWW-050
2 1/2		CIVBFW-065	CIVBFE-065	CIVBFWW-065
3		CIVBFW-080	CIVBFE-080	CIVBFWW-080
4		CIVBFW-100	CIVBFE-100	CIVBFWW-100
5		CIVBFW-125	CIVBFE-125	CIVBFWW-125
6		CIVBFW-150	CIVBFE-150	CIVBFWW-150
8		CIVBFW-200	CIVBFE-200	CIVBFWW-200
10		CIVBFW-250	CIVBFE-250	CIVBFWW-250
12		CIVBFW-300	CIVBFE-300	CIVBFWW-300

Size (in)	PRODUCT CODE			
	Material	Cast Iron	Stainless Steel	Polypropylene
	Seat	PTFE	PTFE	EPDM
Flange	E	E	D	
2		CIVBFWP-050	SSVBFWP-050	PUVBFW-050
2 1/2		CIVBFWP-065	SSVBFWP-065	
3		CIVBFWP-080	SSVBFWP-080	PUVBFW-080
4		CIVBFWP-100	SSVBFWP-100	PUVBFW-100
5			SSVBFWP-125	
6		CIVBFWP-150	SSVBFWP-150	PUVBFW-150
8		CIVBFWP-200	SSVBFWP-200	PUVBFW-200
10		CIVBFWP-250	SSVBFWP-250	
12		CIVBFWP-300	SSVBFWP-300	

## Worm Gear Operated



Size (in)	PRODUCT CODE			
	Material	Cast Iron	Stainless Steel	Polypropylene
	Seat	NBR	EPDM	EPDM
Flange	E	E	E	
2		CIVBFWF-050	SSVBFWF-050	
2 1/2		CIVBFWF-065		
3		CIVBFWF-080	SSVBFWF-080	
4		CIVBFWF-100	SSVBFWF-100	
5		CIVBFWF-125		
6		CIVBFWF-150	SSVBFWF-150	
8		CIVBFWF-200	SSVBFWF-200	PUVBFWF-200
10		CIVBFWF-250		PUVBFWF-250
12		CIVBFWF-300		PUVBFWF-300
14		CIVBFWF-350		PUVBFWF-350
16		CIVBFWF-400		PUVBFWF-400
18		CIVBFWF-450		
20		CIVBFWF-500		
24		CIVBFWF-600		