

Tavlit Threaded Fittings

Application:

High Quality Poly Propylene fittings for irrigation connections.

Features:

- Material: Poly Propylene
- Thread: BSP
- Max working pressure: 1600kpa @ 20°C
- Max working temperature 100°C
- O Ring Seal NBR
- 15-50mm sizes available
- O Ring seal on male and female ends of fittings

Tavlit Hex Nipples



Tavlit Hex Nipples
- Reducing



Tavlit Hex Reducing
Bushes - M / F



Tavlit Couplings
- Reducing



Tavlit Couplings



Tavlit 90° Elbows M / F



Tavlit 90° Elbows



Tavlit Adaptors




Tavlit Tees



Tavlit Caps



Tavlit Plugs



SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE – PRODUCT DRAWINGS / IMAAGES ARE REPRESENTATIVE ONLY AND ARE SUBJECT TO CHANGE.

PERTH

PH: 08 9455 1677
FAX: 08 9455 1680
hrsales@hrproducts.com.au

SYDNEY

PH: 02 9725 5733
FAX: 02 725 5283
infonsw@hrproducts.com.au

MELBOURNE

PH: 03 9457 7500
FAX: 03 9457 7400
infovic@hrproducts.com.au

BRISBANE

PH: 07 3806 0522
FAX: 07 3806 0533
infoqld@hrproducts.com.au

ADELAIDE

PH: 08 8341 0008
FAX: 08 8341 0707
infosa@hrproducts.com.au