

Gibault – PVC Repair Coupling

Application:

Designed for use in the repair of irrigation pipe networks primarily used on UPVC.

Specifications:

- Rubber gasket with taper for positive compression.
- Internal / external corrosion protection with fusion bonded epoxy coating
- Angular deflection of 6° on all sides

Materials:

- Sleeve & Ring – ductile iron
- Rubber gasket – nitrile
- Bolts, washer & nuts – stainless steel
- Coating – fusion bonded epoxy (250 micron)



Operating Specifications:

- Maximum pressure 1600kpa

MODELS	CODE	SERIES 1 PVC PIPE OD MM
80mm	SG80	88.9
100mm	SG100	114.3
150mm	SG150	160.3
200mm	SG200	225.3
250mm	SG250	280.4

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE – PRODUCT DRAWINGS / IMAAGES ARE REPRESENTATIVE ONLY AND ARE SUBJECT TO CHANGE.

PERTH

PH: 08 9455 1677
FAX: 08 9455 1680
hrsales@hrproducts.com.au

SYDNEY

PH: 02 9725 5733
FAX: 02 725 5283
infonsw@hrproducts.com.au

MELBOURNE

PH: 03 9457 7500
FAX: 03 9457 7400
infovic@hrproducts.com.au

BRISBANE

PH: 07 3806 0522
FAX: 07 3806 0533
infoqld@hrproducts.com.au

ADELAIDE

PH: 08 8341 0008
FAX: 08 8341 0707
infosa@hrproducts.com.au