

Gibault – PVC Repair Coupling

Application:

Designed for use in the repair of irrigation pipe networks primarily used on UPVC may also fit Steel, Cast Iron, AC and Ductile Iron pipes used in irrigation.

See chart for sizing.

Specifications:

- Rubber gasket with taper for positive compression.
- Internal / external corrosion protection with fusion bonded epoxy coating
- Angular deflection of 6° on all sides

Materials:

- Sleeve & Ring – ductile iron
- Rubber gasket – nitrile
- Bolts, washer & nuts – stainless steel
- Coating – fusion bonded epoxy (250 micron)



Operating Specifications:

- Maximum pressure 1600kpa

MODELS	CODE	NOMINAL SIZE MM	SEALING RANGE MM
80mm	VG88-103	80	88-103
100mm	VG108-128	100	108-128
150mm	VG159-185	150	159-182
200mm	VG218-235	200	218-235
250mm	VG271-289	250	271-289

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE – PRODUCT DRAWINGS / IMAAGES ARE REPRESENTATIVE ONLY AND ARE SUBJECT TO CHANGE.

PERTH

PH: 08 9455 1677
FAX: 08 9455 1680
hrsales@hrproducts.com.au

SYDNEY

PH: 02 9725 5733
FAX: 02 725 5283
info@hrproducts.com.au

MELBOURNE

PH: 03 9457 7500
FAX: 03 9457 7400
info@hrproducts.com.au

BRISBANE

PH: 07 3806 0522
FAX: 07 3806 0533
info@hrproducts.com.au

ADELAIDE

PH: 08 8341 0008
FAX: 08 8341 0707
info@hrproducts.com.au