## PRODUCT SPECIFICATION

## TAVLIT FILTER 40MM & 50MM

## **Application:**

Used for protection in drip, spray and sprinkler watering systems.

## Features:

- UV resistant
- BSP male & female thread
- High flow, low pressure loss
- Body polypropylene
- Pressure gauge ports (inlet/outlet)
- Gaskets EPDM
- Maximum working pressure 1,000kPa
- Maximum flow 40mm 207 LPM
- Maximum flow 50mm 342 LPM
- Filtration screen polyester/stainless steel screen
- Screen filter area 40mm 552cm<sup>2</sup>
- Screen filter area 50mm 670cm<sup>2</sup>
- 80 mesh (200 micron) Blue
- 120 mesh (130 micron) Brown
- 155 mesh (100 micron) Green



MODELS	CODE
40mm Filter with FxF BSP (120 mesh)	TF-40-120
40mm Filter with MxM BSP (155 mesh)	TF-40-155
40mm Filter with MxM BSP (120 mesh)	TF-40M-120
50mm Filter with FxF BSP (120 mesh)	TF-50-120
50mm Filter with MxM BSP (120 mesh)	TF-50M-120
120 mesh replacement screen 40/50 (brown)	TFF-120
155 mesh replacement screen 40/50 (green)	TFF-155

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE - PRODUCT DRAWINGS / IMAGES ARE REPRESENTATIVE ONLY AND ARE SUBJECT TO CHANGE.

PERTH PH: 08 9455 1677 FAX: 08 9455 1680 hrsales@hrproducts.com.au SYDN EY PH: 02 9725 5733 FAX: 02 725 5283 infonsw@hrproducts.com.au MELBOURNE PH: 03 9457 7500 FAX: 03 9457 7400 infovic@hrproducts.com.au BRISBANE PH: 07 3806 0522 FAX: 07 3806 0533 infoqld@hrproducts.com.au ADELAIDE PH: 08 8341 0008 FAX: 08 8341 0707 infosa@hrproducts.com.au

www.hrproducts.com.au