

## HR - LANDSCAPE DRIPLINE

Suitable for Lawns, shrubs, trees and flower beds. Best suited for level ground applications either on surface or under mulch installations.

### FEATURES

- Suitable for use with standard 13mm LD fittings
- Size 12.5mm ID and 14.5mm OD
- Brown UV protected tubing is durable under sunny conditions and blends with ground or mulch colours.
- Dripline has dual outlet ports on each dripper to ensure that only one outlet has contact with the ground, eliminating a chance of back-siphoning debris into the tubing.
- Manufactured in Australia
- Round dripper with wide water passages which provides high resistance to blockages.
- Two inlet filters per dripper
- Self cleaning, water flow in dripper labyrinth flushes out sediments continuously
- Durable tube for years of trouble free use



### SPECIFICATIONS

- Dripper flow rate 2.0 lph Non Compensating
- Standard dripper spacing of 0.3m available
- Recommended working pressure 50 to 300 kpa
- Maximum single lateral run length 60m
- Recommended filtration 120 mesh
- Coil lengths 50, 100



#### Average dripper flow vs pressure for 2lph

Pressure kpa	50	100	150	200	250	300
Discharge lph	1.50	2.20	2.75	3.20	3.60	3.95

#### MODELS

#### CODE

30cm x 2.1 lph non compensated 100m roll	HRDNPC10030
30cm x 2.1 lph non compensated 50m roll	HRDNPC5030

#### PERTH

PH: 08 9455 1677  
FAX: 08 9455 1680  
hrproducts@bigpond.com.au

#### SYDNEY

PH: 02 9725 5733  
FAX: 02 725 5283  
nsw\_hrproducts@bigpond.com

#### MELBOURNE

PH: 03 9457 7500  
FAX: 03 9457 7400  
vic\_hrproducts@bigpond.com

#### BRISBANE

PH: 07 3290 1200  
FAX: 07 3808 4997  
qld\_hrproducts@bigpond.com

#### ADELAIDE

PH: 08 8341 0008  
FAX: 08 8341 0707  
sa\_hrproducts@bigpond.com